

# POSIFLEX™

Leaders in POS Terminal Technology

## JIVA 8000 Series



### POSIFLEX JIVA 8000 Terminal Series

The JIVA 8000 terminal series is an Intel-based all-in-one touch terminal designed for hospitality, retail and vertical markets that require increased performance at the front-end workstation. Featuring 15" high-luminance resistive or infrared touch panel options to meet any application requirement. With a unique space saving design, the base stand houses a primary hard drive, rear mount bracket for an optional 2nd display and optional built-in UPS battery. The JIVA 8000 optimizes 'WEPOS' - Microsoft Windows Embedded for Point-of-Service for "Plug-n-Play" functionality and is ideal for hospitality, retail, gaming, kiosk, healthcare, c-store, petroleum, grocery, and a variety of vertical markets.

#### JIVA 8000 Features:

- Powerful Intel™ CPU options
- Resistive or infrared touch
- Space saving design
- Optional built-in UPS battery
- Optional 2nd display
- Removable 2.5" HDD in base stand
- Wallmount option



[www.posiflexusa.com](http://www.posiflexusa.com)

Posiflex USA  
30689 Huntwood Avenue,  
Hayward, CA 94544  
Toll-free: 888.968.1668 Phone: 510.429.7097 Fax: 510.475.0982  
e-mail: [sales@posiflexusa.com](mailto:sales@posiflexusa.com)



### ALL JIVA TERMINAL MODELS CAN BUNDLE WITH

- SD200 Series 2-in-1 Attachment MSR and/or U.are.U Finger Print Sensor
- CR6000 Series Cash Drawer
- PP7000 Series Aura Thermal Receipt Printer
- PD2000 Series Pole Display or PD302 Customer Display
- KB6000 Series Programmable Keyboard
- LM6101C Series 2nd LCD Display

| Specifications         |   |                    |
|------------------------|---|--------------------|
| Model                  | JIVA 8015   | JIVA 8415          |
| Max. LCD Resolution:   | 1024 x 768  |                    |
| Brightness:            | 250 nit/m <sup>2</sup>  |                    |
| LCD Panel:             | 15.1" high luminance TFT LCD panel                                      |                    |
| Touch Sensor:          | Resistive or Anti-scratch IR type                                       |                    |
| CPU:                   | Celeron 2.0 GHz   | Pentium P4 2.4 GHz |
| Memory:                | 512 MB (expandable to 2 GB)   |                    |
| Video Memory:          | 16~128 MB shared memory   |                    |
| Audio                  | Standard  |                    |
| Serial Port:           | 4 ports with 5V DC support  |                    |
| Parallel port:         | 1   |                    |
| CR Port:               | 1 port controls 2 devices (under COM1)                                  |                    |
| USB Port:              | 6   |                    |
| KB Port:               | 1 x PS/2 type   |                    |
| Mouse Port:            | 1 x PS/2 type   |                    |
| Lan Port:              | 10/100 MHz base Ethernet  |                    |
| HDD:                   | 2.5" HDD, 40GB up   |                    |
| FDD:                   | 2.5" external USB interface (optional)                                  |                    |
| OS Support:            | Microsoft Windows XP Professional / WEPOS                               |                    |
| Compact Flash Port:    | N/A   |                    |
| Internal UPS:          | Yes (Battery Optional)  |                    |
| ON/OFF Control:        | Software controlled for Mechanical ON/OFF or Mechanical ON Software OFF |                    |
| Tilt Adjustment:       | From 17.5° to 87.5°   |                    |
| Mounting Option:       | Table top or Wall mountable (optional)                                  |                    |
| Housing Color:         | Black   |                    |
| Power Supply:          | Input 100~240V, output 12V/150W AC adaptor                              |                    |
| Dimension:             | 14.8"(W) x 11.1"(D) x 11.7~14.7"(H)                                     |                    |
| Safety Certifications: | PSU: UL / VDE / T mark Terminal: FCC, CE (meet IEC 100-4-2 class A)     |                    |

### About POSIFLEX

Established in 1984, Posiflex has grown to be recognized as a leading provider of innovative Point-of Service (POS) hardware and platform technology used in diverse markets. Posiflex partners with applications software developers to provide reliable POS terminal systems to the hospitality, healthcare, medical, retail and specialized markets. The Company's products are sold through industry specialists, value-added resellers and distributors. All products are designed and manufactured in Taipei, Taiwan in two ISO 9001/9002/14001 certified laboratories and factories. Posiflex USA is located in Hayward, California. For additional information on Posiflex and the diverse product line, visit [www.posiflexusa.com](http://www.posiflexusa.com) or call (888) 968 -1668.

### JIVA 8000 Series with Slim Type Base Stand

|  |   |
|--|---|
|  |   |
| Rear mount bracket for optional 2 <sup>nd</sup> display  | Built-in removable 2.5" HDD in base stand |
|  |   |
| Rear mount bracket for optional pole display (PD Series) | Optional built-in battery                 |

### Available Peripherals

|                                       |  |
|---------------------------------------|--|
|                                       |  |
| Integrated 2-in-1 MSR attachment      | Aura thermal receipt printer (PP series) |
|                                       |  |
| POS programmable keyboard (KB series) | Cash drawer (CR series)                  |

**POSIFLEX™**

30689 Huntwood Avenue,  
Hayward, CA 94544  
Toll-free: 888.968.1668  
Phone: 510.429.7097  
Fax: 510.475.0982  
e-mail: [sales@posiflexusa.com](mailto:sales@posiflexusa.com)